

**Product Information**

**3.9 mm LED Video Panel (Combo Sizing)**

GL2-039IB-T/S

**Indoor Series**

*Semi Front Serviceable*



**Specifications**

**Display**

	TALL	SQUARE
Pixel Pitch	3.91	
LED Type	SMD	
LED Configuration	3-in-1	
Brightness (Nits)	900	
Pixel Count	128 x 256	128 x 128
Pixel Density / Sq M	65,536	
Frame Rate	60 Hz	
Refresh Rate	> 1920K	(adjustable)
Operating Frequency	18.75 MHz	
Gray Scale	16 Bit	
Horizontal Viewing Angle	160 degrees	
Vertical Viewing Angle	120 degrees	
Color Temp Range	6500-9000K	

**Chassis / Exterior**

	TALL		SQUARE	
Width	500 mm	19.69 in	500 mm	19.69 in
Height	1000 mm	39.37 in	500 mm	19.69 in
Depth	75 mm	2.95 in	75 mm	2.95 in
Weight	13.7 kg	30.2 lbs	8.7 kg	19.1 lbs
Material	Die-cast aluminum		Die-cast aluminum	
Load Cap.	200 kg	440 lb	200 kg	440 lb

**Power**

Input voltage	220V/110V			
Average Pwr	140W/panel	280W/sq m	70W/panel	280W/sq m
Max Pwr	280W/panel	560W/sq m	140W/panel	560W/sq m
Input Current	2.9 A AC 1.4A			