

Product Information

3.9 mm & 4.8 mm LED Video Panel

Outdoor+Indoor Series

GMX-0390W
GMX-0480W

We have been searching for a high brightness outdoor 4.8 and 3.9 mm panel with the quality and durability we and you need – and here is the series we've been waiting for.

IP65 Rated



Specifications

Display

	4.8 mm	3.9 mm
Pixel Pitch	4.81	3.91
LED Type	SMD	
LED Configuration	3-in-1	
Brightness (Nits)	4500 BLK 4500 WHT	4500 BLK 5250 WHT
Pixel Count	104 x 104	128 x 128
Pixel Density / Sq M	43264	65536
Frame Rate	60 Hz	
Refresh Rate	> 1000 Hz	
Scan	1/8	1/13
Gray Scale	16 Bit	
Horizontal Viewing Angle	140	
Vertical Viewing Angle	140	
Color Temp Range	6500-9500K	

Available with black surface LED's or white masked LED's

Chassis / Exterior

Width	500 mm	19.69 in
Height	500 mm	19.69 in
Depth	75 mm	2.95 in
Weight	9 kg	19.8 lbs

Material Die cast aluminum alloy

Power

Input voltage	220V/110V	
Average Pwr	70W/panel	280W/sq m
Max Pwr	140W/panel	560W/sq m
Input Current	1.6A	est

